




NOFMANN C O P E N H A G E N

Grant Pendant Ø23 cm - EU Version





DESCRIPTION

The Grant pendant lamps in two sizes provide ample opportunity for lighting up spaces of various size and character. Due to the dispersion lens, the pendants can be hung high without blinding. An aesthetic and spaceoptimizing lighting solution, the Grant wall lamps have arms that move from right to left and lampshades that can be tipped up and down, allowing the lamps to take up several different positions.

DESIGN Simon Legald, 2018

MATERIAL Brass Plated Steel / Black Plated Steel / Granite

CONSTRUCTION

The six versions of Grant collection are constructed with a replaceable low-energy LED light source with dispersion lens, which is attached with small brass finger screws. The wall lamp versions can move from side to side (ca. 180 degrees). A ball joint connection on the table and floor lamp allows the lampshades to be positioned in diverse directions.

MAINTENANCE

Clean with damp cloth. Avoid use of all-prupose cleaners and other degreasing detergents.

CORD 4 m textile cord, black color.

CANOPY Included, black color, H: 7,7 x Ø: 9 cm 0,04 kg

DIMMABLE FUNCTION

Yes. Ensure your dimmer is compatible with LED.

VOLTAGE 220-240 V

MAX LOAD 7 W

FREQUENCY 50/60 Hz


IP RATING IP20

CLASSIFICATION Class II

SOCKET GX53

LIGHT SOURCE - INCLUDED LED included: GX53 Art. No.: 502028 Power: 5W±10% CCT: 3 000 K Output: 400 Im ±10% Life Span: 15000-20 000 CRI: ~80

GENERAL STANDARD & CERTIFICATES EN 55015:2013 EN 55015:2013+A1:2015 EN 61547:2009 EN 61000-3-2:2014 EN 61000-3-3:2013










Grant Pendant Ø45 cm - EU Version





DESCRIPTION

The Grant pendant lamps in two sizes provide ample opportunity for lighting up spaces of various size and character. Due to the dispersion lens, the pendants can be hung high without blinding. An aesthetic and spaceoptimizing lighting solution, the Grant wall lamps have arms that move from right to left and lampshades that can be tipped up and down, allowing the lamps to take up several different positions.

DESIGN Simon Legald, 2018

MATERIAL Brass Plated Steel / Black Plated Steel / Granite

CONSTRUCTION

The six versions of Grant collection are constructed with a replaceable low-energy LED light source with dispersion lens, which is attached with small brass finger screws. The wall lamp versions can move from side to side (ca. 180 degrees). A ball joint connection on the table and floor lamp allows the lampshades to be positioned in diverse directions.

MAINTENANCE

Clean with damp cloth. Avoid use of all-prupose cleaners and other degreasing detergents.

CORD 4m textile cord, black color.

CANOPY Included, black color, H: 7,7 x Ø: 9 cm 0,04 kg

DIMMABLE FUNCTION

Yes. Ensure your dimmer is compatible with LED.

VOLTAGE 220-240 V

MAX LOAD 7 W

FREQUENCY 50/60 Hz


IP RATING IP20

CLASSIFICATION Class II

SOCKET GX53

LIGHT SOURCE - INCLUDED LED included: GX53 Art. No.: 502029 Power: 7W±10% CCT: 3 000 K Output: 610 lm ±10% Life Span: 15000-20 000 CRI: ~80

GENERAL STANDARD & CERTIFICATES EN 55015:2013 EN 55015:2013+A1:2015 EN 61547:2009 EN 61000-3-2:2014 EN 61000-3-3:2013








Brass / Granite



Grant Table Lamp - EU Version





DESCRIPTION

The Grant table lamp is a sophisticated desk lamp for the home office, but equally fit for the bedside table or living room sideboard. Tilt the lampshade up and down to direct the light and scroll on the cord's dimmer switch to go from soft ambience light to a bright reading light.

DESIGN Simon Legald, 2018

MATERIAL

Brass Plated Steel / Black Plated Steel / Granite

CONSTRUCTION

The six versions of Grant collection are constructed with a replaceable low-energy LED light source with dispersion lens, which is attached with small brass finger screws. The wall lamp versions can move from side to side (ca.180 degrees). A ball joint connection on the table and floor lamp allows the lampshades to be positioned in diverse directions.

MAINTENANCE

Clean with damp cloth. Avoid use of all-prupose cleaners and other degreasing detergents.

CORD 4m textile cord with switch, black color.

DIMMABLE FUNCTION Yes. VOLTAGE 220-240 V

MAX LOAD 7 W

FREQUENCY 50/60 Hz


IP RATING IP20

CLASSIFICATION Class II

SOCKET GX53

LIGHT SOURCE - INCLUDED LED included: GX53 Art. No.: 502027 Power: 4W±10% CCT: 3 000 K Output: 300 Im ±10% Life Span: 15000-20 000 CRI: ~80

GENERAL STANDARD & CERTIFICATES EN 55015:2013 EN 55015:2013+A1:2015 EN 61547:2009 EN 61000-3-2:2014 EN 61000-3-3:2013







Grant Floor Lamp - EU Version





136 cm

DESCRIPTION

Sharing the same features as the Grant table lamp, an adjustable shade and dimmer switch, the Grant floor lamp is ideal as a reading lamp or for lighting up dark corners.

DESIGN Simon Legald, 2018

MATERIAL

Brass Plated Steel / Black Plated Steel / Granite

CONSTRUCTION

The six versions of Grant collection are constructed with a replaceable low-energy LED light source with dispersion lens, which is attached with small brass finger screws. The wall lamp versions can move from side to side (ca. 180 degrees). A ball joint connection on the table and floor lamp allows the lampshades to be positioned in diverse directions.

MAINTENANCE

Clean with damp cloth. Avoid use of all-prupose cleaners and other degreasing detergents.

CORD

4m textile cord with switch, black color.

DIMMABLE FUNCTION Yes.

VOLTAGE 220-240 V

MAX LOAD 7 W

FREQUENCY 50/60 Hz


IP RATING IP20

CLASSIFICATION Class II

SOCKET GX53

LIGHT SOURCE - INCLUDED LED included: GX53 Art. No.: 502027 Power: 4VV±10% CCT: 3 000 K Output: 300 Im ±10% Life Span: 15000-20 000 CRI: ~80

GENERAL STANDARD & CERTIFICATES EN 55015:2013 EN 55015:2013+A1:2015 EN 61547:2009 EN 61000-3-2:2014 EN 61000-3-3:2013






COLOR



Black / Granite





DESCRIPTION

An aesthetic and space-optimizing lighting solution, the Grant wall lamps have arms that move from right to left and lampshades that can be tipped up and down, allowing the lamps to take up several different positions.

DESIGN Simon Legald, 2018

MATERIAL Brass Plated Steel / Black Plated Steel / Granite

CONSTRUCTION

The six versions of Grant collection are constructed with a replaceable low-energy LED light source with dispersion lens, which is attached with small brass finger screws. The wall lamp versions can move from side to side (ca. 180 degrees). A ball joint connection on the table and floor lamp allows the lampshades to be positioned in diverse directions.

MAINTENANCE

Clean with damp cloth. Avoid use of all-prupose cleaners and other degreasing detergents.

CORD 4m textile cord with switch, black color.

DIMMABLE FUNCTION Yes.

VOLTAGE 220-240 V

MAX LOAD 7 W

FREQUENCY 50/60 Hz


IP RATING IP20

CLASSIFICATION Class II

SOCKET GX53

LIGHT SOURCE - INCLUDED LED included: GX53 Art. No.: 502027 Power: 4W±10% CCT: 3 000 K Output: 300 Im ±10% Life Span: 15000-20 000 CRI: ~80

GENERAL STANDARD & CERTIFICATES EN 55015:2013 EN 55015:2013+A1:2015 EN 61547:2009 EN 61000-3-2:2014 EN 61000-3-3:2013








Grant Wall Lamp 111 cm - EU Version





III cm

DESCRIPTION

An aesthetic and space-optimizing lighting solution, the Grant wall lamps have arms that move from right to left and lampshades that can be tipped up and down, allowing the lamps to take up several different positions.

DESIGN Simon Legald, 2018

MATERIAL Brass Plated Steel / Black Plated Steel / Granite

CONSTRUCTION

The six versions of Grant collection are constructed with a replaceable low-energy LED light source with dispersion lens, which is attached with small brass finger screws. The wall lamp versions can move from side to side (ca. 180 degrees). A ball joint connection on the table and floor lamp allows the lampshades to be positioned in diverse directions.

MAINTENANCE

Clean with damp cloth. Avoid use of all-prupose cleaners and other degreasing detergents.

CORD

4 m textile cord with switch, black color.

DIMMABLE FUNCTION Yes.

VOLTAGE 220-240 V

MAX LOAD 7 W

FREQUENCY 50/60 Hz


IP RATING IP20

CLASSIFICATION Class II

SOCKET GX53

LIGHT SOURCE - INCLUDED LED included: GX53 Art. No.: 502027 Power: 4W±10% CCT: 3 000 K Output: 300 Im ±10% Life Span: 15000-20 000 CRI: ~80

GENERAL STANDARD & CERTIFICATES EN 55015:2013 EN 55015:2013+A1:2015 EN 61547:2009 EN 61000-3-2:2014 EN 61000-3-3:2013











NOFMANN C O P E N H A G E N

Grant Pendant Ø23 cm - US Version





DESCRIPTION

The Grant pendant lamps in two sizes provide ample opportunity for lighting up spaces of various size and character. Due to the dispersion lens, the pendants can be hung high without blinding. An aesthetic and spaceoptimizing lighting solution, the Grant wall lamps have arms that move from right to left and lampshades that can be tipped up and down, allowing the lamps to take up several different positions.

DESIGN Simon Legald, 2018

MATERIAL Brass Plated Steel / Black Plated Steel / Granite

CONSTRUCTION

The six versions of Grant collection are constructed with a replaceable low-energy LED light source with dispersion lens, which is attached with small brass finger screws. The wall lamp versions can move from side to side (ca. 180 degrees). A ball joint connection on the table and floor lamp allows the lampshades to be positioned in diverse directions.

MAINTENANCE

Clean with damp cloth. Avoid use of all-prupose cleaners and other degreasing detergents.

Black /

Granite

CORD 4 m textile cord, black color.

CANOPY Included, black color, H: 7,7 x Ø: 9 cm 0,04 kg

DIMMABLE FUNCTION

Yes - Ensure your dimmer is compatible with LED.

COLOR

Brass / Granite

VOLTAGE

120V

MAX LOAD 7 W


FREQUENCY 60 Hz

IP RATING IP20

CLASSIFICATION Class I

SOCKET GX53


LIGHT SOURCE - INCLUDED LED included: GX53 Art. No.: 502028 Power: 5W±10% CCT: 3 000 K Output: 400 Im ±10% Life Span: 15000-20 000 CRI: ~80





Grant Pendant Ø45 cm - US Version





DESCRIPTION

The Grant pendant lamps in two sizes provide ample opportunity for lighting up spaces of various size and character. Due to the dispersion lens, the pendants can be hung high without blinding. An aesthetic and spaceoptimizing lighting solution, the Grant wall lamps have arms that move from right to left and lampshades that can be tipped up and down, allowing the lamps to take up several different positions.

DESIGN Simon Legald, 2018

MATERIAL Brass Plated Steel / Black Plated Steel / Granite

CONSTRUCTION

The six versions of Grant collection are constructed with a replaceable low-energy LED light source with dispersion lens, which is attached with small brass finger screws. The wall lamp versions can move from side to side (ca. 180 degrees). A ball joint connection on the table and floor lamp allows the lampshades to be positioned in diverse directions.

MAINTENANCE

Clean with damp cloth. Avoid use of all-prupose cleaners and other degreasing detergents.

CORD 4 m textile cord, black color.

CANOPY Included, black color, H: 7,7 x Ø: 9 cm 0,04 kg

DIMMABLE FUNCTION

Yes - Ensure your dimmer is compatible with LED.

COLOR

Brass / Granite

Black / Granite

VOLTAGE I 20 V

MAX LOAD 7 W


FREQUENCY 60 Hz

IP RATING IP20

CLASSIFICATION Class I

SOCKET GX53


LIGHT SOURCE - INCLUDED LED included: GX53 Art. No.: 502029 Power: 7W±10% CCT: 3 000 K Output: 610 lm ±10% Life Span: 15000-20 000 CRI: ~80





Grant Table Lamp - US Version





DESCRIPTION

The Grant table lamp is a sophisticated desk lamp for the home office, but equally fit for the bedside table or living room sideboard. Tilt the lampshade up and down to direct the light and scroll on the cord's dimmer switch to go from soft ambience light to a bright reading light.

DESIGN Simon Legald, 2018

MATERIAL

Brass Plated Steel / Black Plated Steel / Granite

CONSTRUCTION

The six versions of Grant collection are constructed with a replaceable low-energy LED light source with dispersion lens, which is attached with small brass finger screws. The wall lamp versions can move from side to side (ca. 180 degrees). A ball joint connection on the table and floor lamp allows the lampshades to be positioned in diverse directions.

MAINTENANCE

Clean with damp cloth. Avoid use of all-prupose cleaners and other degreasing detergents.

CORD 4m textile cord with switch, black color.

DIMMABLE FUNCTION Yes. VOLTAGE 120 V

MAX LOAD 7 W


FREQUENCY 60 Hz

IP RATING IP20

CLASSIFICATION Class I

SOCKET GX53

LIGHT SOURCE - INCLUDED LED included: GX53 Art. No.: 502027 Power: 4VV±10% CCT: 3 000 K Output: 300 lm ±10% Life Span: 15000-20 000 CRI: ~80







Grant Floor Lamp - US Version





E 136

DESCRIPTION

Sharing the same features as the Grant table lamp, an adjustable shade and dimmer switch, the Grant floor lamp is ideal as a reading lamp or for lighting up dark corners.

DESIGN Simon Legald, 2018

MATERIAL Brass Plated Steel / Black Plated Steel / Granite

CONSTRUCTION

The six versions of Grant collection are constructed with a replaceable low-energy LED light source with dispersion lens, which is attached with small brass finger screws. The wall lamp versions can move from side to side (ca.180 degrees). A ball joint connection on the table and floor lamp allows the lampshades to be positioned in diverse directions.

MAINTENANCE

Clean with damp cloth. Avoid use of all-prupose cleaners and other degreasing detergents.

CORD 4m textile cord with switch, black color.

DIMMABLE FUNCTION Yes.

VOLTAGE 120 V


MAX LOAD 7 W

FREQUENCY 60 Hz

IP20

Class I

LIGHT SOURCE - INCLUDED LED included: GX53 Art. No.: 502027










IP RATING

CLASSIFICATION

SOCKET GX53

> Power: 4W±10% CCT: 3 000 K Output: 300 lm ±10% Life Span: 15000-20000 CRI:~80





DESCRIPTION

An aesthetic and space-optimizing lighting solution, the Grant wall lamps have arms that move from right to left and lampshades that can be tipped up and down, allowing the lamps to take up several different positions.

DESIGN Simon Legald, 2018

MATERIAL Brass Plated Steel / Black Plated Steel / Granite

CONSTRUCTION

The six versions of Grant collection are constructed with a replaceable low-energy LED light source with dispersion lens, which is attached with small brass finger screws. The wall lamp versions can move from side to side (ca. 180 degrees). A ball joint connection on the table and floor lamp allows the lampshades to be positioned in diverse directions.

MAINTENANCE

Clean with damp cloth. Avoid use of all-prupose cleaners and other degreasing detergents.

CORD 4 m textile cord with switch, black color.

DIMMABLE FUNCTION Yes.

VOLTAGE 120 V

MAX LOAD 7 W


FREQUENCY 60 Hz

IP RATING IP20

CLASSIFICATION Class I

SOCKET GX53

LIGHT SOURCE - INCLUDED LED included: GX53 Art. No.: 502027 Power: 4W±10% CCT: 3 000 K Output: 300 Im ±10% Life Span: 15000-20 000 CRI: ~ 80










Grant Wall Lamp 111 cm - US Version





III cm

DESCRIPTION

An aesthetic and space-optimizing lighting solution, the Grant wall lamps have arms that move from right to left and lampshades that can be tipped up and down, allowing the lamps to take up several different positions.

DESIGN Simon Legald, 2018

MATERIAL Brass Plated Steel / Black Plated Steel / Granite

CONSTRUCTION

The six versions of Grant collection are constructed with a replaceable low-energy LED light source with dispersion lens, which is attached with small brass finger screws. The wall lamp versions can move from side to side (ca. 180 degrees). A ball joint connection on the table and floor lamp allows the lampshades to be positioned in diverse directions.

MAINTENANCE

Clean with damp cloth. Avoid use of all-prupose cleaners and other degreasing detergents.

CORD 4m textile cord with switch, black color.

DIMMABLE FUNCTION Yes.

VOLTAGE 120 V

MAX LOAD 7 W

FREQUENCY 60 Hz

IP RATING IP20

CLASSIFICATION Class I

SOCKET GX53

LIGHT SOURCE - INCLUDED LED included: GX53 Art. No.: 502027 Power: 4VV±10% CCT: 3 000 K Output: 300 lm ±10% Life Span: 15000-20 000 CRI: ~80

